



HbA1c Analytical Column (1000)





TRINITY BIOTECH KANSAS CITY, MO 64132 USA w.trinitybiotech.com



30 DAYS MAX

-28°C





2°C



13872 2026-03-31

09-06-0046 CONT 1 Each

EC REP

Trinity Biotech plc Bray, Co. Wicklow, Ireland Tel: +353 1 276 9800 Fax: +353 1 276 9888

Certificate of Analysis

Production Date

2023-03-01

Intended Use

Quality Control

This analytical column is intended for use with the Premier Hb9210 HbA1c Analyzer only. No substitutions are permitted, registered, cleared or authorized. No other uses are intended, registered, cleared or authorized.

The Premier Hb9210 system is intended for the quantitative measurement of hemoglobin A1c (HbA1c) in human capillary and venous whole blood. HbA1c is used for the monitoring of long-term glycemic control in individuals with diabetes mellitus. For in vitro diagnostic use only. IVD

	monitae. Tot in via e diagnostic dec on	.yv.b_		
	09-06-0046 Lot 13872			
Performance Analysis				
	DASEI INE	ACCEPTABILITY		
Standard		deflection higher than 5 mm above		
Stanuaru	n	ormal.		
Result		vith no deflection on the printed		
	chromatogram greater t	than 5mm above the normal.		
		PHY ACCEPTABILITY		
Standard		shape, resolution and separation good.		
Result		ated peak shape, resolution and		
	separati	on are good.		
	ACCURACY AND LINEARITY			
Standard	with	ceability to IFCC standards) recovery nin limits.		
Result	The calibrator and control re-	covery is within acceptable limits.		
	RETENTION TIME – PEAK 1			
Standard	Peak 1 recovery between 0.20 and 0.30 Minutes.			
Result	The recovery of peak 1 is t	petween 0.20 and 0.30 minutes .		
		N TIME – PEAK 2		
Standard	Peak 2 recovery between 0.58 and 0.68 Minutes.			
Result	The recovery of peak 2 is between 0.58 and 0.68 minutes			
	DRIFT - %HbA1c WITH CALIBRATOR 1			
Standard	Standard drift 0.0 to 0.2			
Result	The standard drift is between 0.0 and 0.2.			
	DRIFT - %HbA1c WITH CALIBRATOR 2			
Standard	Standard Drift 0.0 to 0.3			
Result	The standard drift is between 0.0 and 0.3			
		ACTIVITY ACCEPTABILITY		
Standard	Acceptable total peak area count for C-trait and normal patient sample.			
Result	The total peak area count for C-trait and normal patient sample is acceptable.			
AUTHORIZED REPRESENTATIVE APPROVAL				
Mela	nu kankin	Date: 107303-09		
1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	THE PERSON NAMED IN COLUMN TWO IS NOT THE OWNER.			

HbA1c - Assessment of hemoglobin A1c has proven useful in the control of diabetes.

Analytical column is performance validated to assure accuracy and precision with the Trinity Biotech assay and system for the measurement of hemoglobin A1c.

Column is ready for use.



Important Information Immediately following each column change, please verify that the baseline is smooth and quiet prior to running calibration. Do not proceed if excessive noise is present. Please refer to the system Operator's Manual chapter for "Chromatography" for additional information regarding column change verification and baseline verification checks.

STORAGE AND STABILITY

Store at 2 – 8°C for long term storage. Do not allow to freeze.

Columns that are refrigerated at 2-8°C are stable until the noted expiry when kept tightly closed. Columns that are placed into service have a limited shelf life and will be gradually consumed once opened, including when removed from the system. Refer to the Column Life section below for details.



EXP See the column label for the expiration date. **DO NOT USE** after the expiration date.

PRECAUTIONS

For in vitro diagnostic use only. Avoid skin contact. Consult the product MSDS for safety information. This column is used in conjunction with blood testing equipment and warrants handling under universal precaution procedures for safety.

ORDERING INFORMATION

Reference No.	Item	Quantity
09-06-0046	Premier Hb9210 HbA1c Analytical Column	1 each

COLUMN LIFE

Column life will vary depending on diligence in:

- System maintenance (regular and preventative maintenance, as scheduled and using manufacturer-specified items),
- Column maintenance (frit changes, proper shutdowns (nightly/weekends) with WASH reagent to preserve the column),
- Reagent management (closed containers, no topping-off, and replacement of fouled check-valves if reagent is allowed to run dry), and/or
- Calibrator and control management (careful preparation according to PI reconstitution instructions, careful preservation according to PI instructions). *Note: Use of alternate control materials, not supplied by Trinity Biotech, may result in control drift and reduced column life and thereby voids any implied or written column performance or column life warranty.

Additionally, column life will vary depending on weekly test throughput (low throughput and infrequentlyused systems may not achieve the average number injections)

Any series of columns experiencing reduced life on the same instrument is indication of a system or operation issue (or very low weekly test throughput). Systems in need of routine or preventive maintenance will experience reduced column life. For these systems, although changing the column provides improvement, it is not the cause, and short column life will continue until the issue is properly

NOTE: Column warranty claims must include the following supporting information: maintenance schedule (date of last PM), column change report (or cycle count) report, chromatography (including cover page and header information), the number of injections, and any follow-up information requests made. Any claim with missing information, as specified above, cannot be processed.

Pour d'autres langues Für andere Sprachen Para otras lenguas Per le altre lingue Dla innych iezyków

Para outras línguas Για τις άλλες λώσσες För andra språk For andre språk

www.trinitvbiotech.com

For other languages, please contact your local distributor.



Trinity Biotech Kansas City, MO 64132 USA



Trinity Biotech plc Bray Co. Wicklow, Ireland Tel. 353 1 2769800 Fax 353 1 2769888 www.trinitybiotech.com



